

# STRIP LED

LX-ST-D3120-24V-8mm



<b>IP</b> 55/65/67	<b>CRI</b> >80	<b>DC24V</b>
-----------------------	-------------------	--------------



## STRIP LED

High cost performance

High density lamp, more uniform light

Provide 4 white light options for 2700-6500K

Mounting : 3M tape

On-off times : 10000 (test times)



**luxio**  
L I G H T I N G

[www.luxio-lighting.com](http://www.luxio-lighting.com)

## References

Reference	Led Power	Max Power	Luminous flux	CCT/K	IP Rating	Dimensions
LX-ST-D3120-24V-8mm	8.4W(1m)	9.6W(1m)	655Lm	2300k	IP55/IP65/IP67	5000*8*1.8mm
			701Lm	2700K		
			739Lm	3000K		
			762Lm	4000K		
			739Lm	6000K		

## Accessories Information

Name	Picture	Code	description
Connector for wire and FPC		LX-94-03-00-0037	10mm width, 2PIN connector of wire and FPC,suitable for white color strip, NO/NA,2PIN wire 18- 22AWG
Connector for FPC and FPC		LX-94-42-621020004	10mm width, 2PIN connector of FPC and FPC,suitable for white color strip,NO/NA
Fixed Clip		LX-94-02-00-0018	transparent, 3*8mm self-tapping screws, suitable for 10mm FPC, NO/NA LED strip
Fixed Clip		LX-94-02-00-0016	Fixed clip, transparent, 3*8mm self-tapping screws, suitable for 10mm FPC, SG LED strip
Fixed Clip		LX-94-02-00-0003	Silicone clip, screw: PA 3*8mm, suitable for 10mm FPC,EH/EF/ET strip
Silicone end cap set		LX-94-02-00-0022	Silicone end cap set, including end cap and plug, suitable for 10mm FPC,EH/ET/EF silicone extrusion strip
Mounting groove		LX-94-02-00-0025	Transparent PVC mounting groove,suitable for 10mm FPC,silicone extruded EF/ET strip
Stopper glue		LX-94-16-03010001	Silicone gel, suitable for ST/ET/EH/EF/SF waterproof LED strip

## Dimensions

