

# STRIP LED



LX-ST-D8140SWW-24V-10mm

<b>IP</b> 20/65	<b>CRI</b> >90	<b>DC24V</b>
--------------------	-------------------	--------------



## STRIP LED

Three-wire adjustable toning strip makes it widely match all kinds of controllers

Self-encapsulated design offers six optional 2700-6000K white lights

High quality FPC, high thermal 3M adhesive

Ta: -25~40°C ; Tc : 75°C (max)






**luxio**  
L I G H T I N G

[www.luxio-lighting.com](http://www.luxio-lighting.com)

## References

Reference	Led Power	Max Power	Luminous flux	CCT/K	IP Rating	Dimensions
LX-ST-D8140SWW -24V-10mm	17.1W(1m) 76.8W( 5m)	19.2W(1m)	1710Lm	2700-6000K	IP20/IP65	5000×10×1.5mm
			830Lm	2700K		
			880Lm	6000K		

## Accessories Information

Name	Picture	Code	Description
CCT set		LX-23-01-00-0005	M2+M4-5A Input voltage : 12-24VDC Maximum loaded current : 5A*4CH Max 20A Maximum loaded power:240W/480W(12V/24V)
Connector for FPC and FPC		LX-94-03-00-0041	10mm width, 3PIN connector of wire and FPC, suitable for dual color strip, NO/NA, 3PIN wire 18- 22AWG
Connector for wire and FPC		LX-94-03-00-0042	10mm width, 3PIN connector of FPC and FPC, suitable for dual color strip, NO/NA

## Dimensions

