

STRIP LED



LX-ST-D8192-24V-15mm

IP	CRI	DC24V
20/55/65/67/68	80/90/95	



STRIP LED

Luminance efficiency up to 155LM/W

Self-encapsulated design offers eight optional 1900-6000K white lights

Ta: -25~40°C ; Tc : 75°C (max)

Rated current : 0.67A(1m) /2.7A(5m)



luxio
L I G H T I N G

www.luxio-lighting.com

References

Reference	Led Power	Max Power	Luminous flux	CRI	CCT/K	IP Rating	Dimensions
LX-ST-D8192-24V -15mm	18.9W/(1m) & 64.8W/4m	20.8W(1m)	2220Lm/m	RA>80	1900K	IP20/IP55/IP67 /IP68	4000*15*1.5mm
			2470Lm/m		2300K		
			2670Lm/m		2700K		
			2810Lm/m		3000K		
			2855Lm/m		3500K		
			2930Lm/m		4000K		
			2930Lm/m		5000K		
			2810Lm/m		6000K		
			1780Lm/m	RA>90	1900K		
			1980Lm/m		2300K		
			2140Lm/m		2700K		
			2250Lm/m		3000K		
			2285Lm/m		3500K		
			2345Lm/m		4000K		
			2345Lm/m		5000K		
			2250Lm/m		6000K		
			1760Lm/m	RA>95	1900K		
			1960Lm/m		2300K		
			2120Lm/m		2700K		
			2230Lm/m		3000K		
			2290Lm/m		3500K		
			2325Lm/m		4000K		
			2325Lm/m		5000K		
			1700Lm/m		525nm		
378Lm/m	470nm						

Dimensions

